

# Solutions to Reinforced Concrete Design Problems

Civil Engineering Licensure Exam – Mock Exam

February 26, 2025

## Problem 1: Area of Steel in a Singly Reinforced Concrete Beam

Determine the required area of steel reinforcement ( $A_s$ ) for a singly reinforced concrete beam subjected to a bending moment of 150 kN·m. The beam has a width ( $b$ ) of 300 mm, an effective depth ( $d$ ) of 500 mm, and the concrete compressive strength ( $f'_c$ ) is 25 MPa. Assume the yield strength of steel ( $f_y$ ) is 415 MPa.

**Solution:**

The required area of steel reinforcement can be calculated using:

$$A_s = \frac{M_u}{0.87f_yjd}$$

where: -  $M_u = 150 \times 10^6$  N·mm (factored moment) -  $j = 0.9$  (lever arm factor, commonly approximated as 0.9 for preliminary design)

Substituting values:

$$A_s = \frac{150 \times 10^6}{0.87 \times 415 \times 0.9 \times 500} \approx 923.44 \text{ mm}^2$$

**Reference:** Singly Reinforced Concrete Beam Problem 1

## Problem 2: Longitudinal Reinforcement in a Reinforced Concrete Column

Design the longitudinal reinforcement for a short, axially loaded reinforced concrete column with a square cross-section of 400 mm x 400 mm. The column is subjected to a factored axial load of 2000 kN. Assume  $f'_c = 30$  MPa and  $f_y = 500$  MPa.

**Solution:**

The required area of longitudinal steel ( $A_{st}$ ) is:

$$A_{st} = \frac{P_u - 0.4f'_c A_g}{0.6f_y}$$

where: -  $P_u = 2000 \times 10^3$  N (factored axial load) -  $A_g = 400 \times 400 = 160,000$  mm<sup>2</sup> (gross area of column)

Substituting values:

$$A_{st} = \frac{2000 \times 10^3 - 0.4 \times 30 \times 10^6 \times 160,000}{0.6 \times 500 \times 10^3} \approx 3,333.33 \text{ mm}^2$$

**Reference:** Concrete Column Axial Design (ACI 318-19)

### Problem 3: Shear Capacity of a Reinforced Concrete Beam

A reinforced concrete beam has a width of 300 mm and an effective depth of 500 mm. The concrete compressive strength is 25 MPa. Calculate the shear capacity ( $V_c$ ) of the concrete.

**Solution:**

The shear capacity ( $V_c$ ) of concrete can be determined using:

$$V_c = 0.17\sqrt{f'_c}bd$$

Substituting values:

$$V_c = 0.17 \times \sqrt{25} \times 300 \times 500 \approx 318.2 \text{ kN}$$

**Reference:** Shear Strength of Reinforced Concrete Beams per ACI 318-02

### Problem 4: One-Way Slab Thickness Requirement

Determine the minimum thickness required for a simply supported one-way slab with a span of 4 m to satisfy deflection limits.

**Solution:**

From ACI Code recommendations:

$$\text{Minimum thickness} = \frac{\text{Span}}{L/d}$$

For a simply supported slab,  $L/d = 20$ :

$$\text{Required thickness} = \frac{4000}{20} = 200 \text{ mm}$$

**Reference:** ACI 318-11: Minimum Thickness of Beams and One-Way Slabs

## Problem 5: Development Length of Reinforcement

Calculate the development length required for a 16 mm diameter reinforcing bar in tension. Assume  $f_y = 415$  MPa and  $f'_c = 25$  MPa.

**Solution:**

The development length ( $L_d$ ) is:

$$L_d = \frac{f_y \phi}{4\sqrt{f'_c}}$$

Substituting values:

$$L_d = \frac{415 \times 16}{4 \times \sqrt{25}} = \frac{6640}{20} = 332 \text{ mm}$$

**Reference:** Rebar Development Length Calculator to ACI 318